
## **ALL IN ONE STREET LIGHTS**



## **ALL IN ONE 40 W**

- The perfect solution to illuminate gardens, walks, parking areas...
- Fully automatic, already pre-assembled to be immediately fixed on a pole and ready to work
- Single lamp body in aluminum, extremely compact and light
- 15°/25°/35° adjustable bracket


- Remote control
- LED Lifespan > 100000 hours
- Intelligent operation: lights automatically turn on at dusk and turn off at dawn.\*

\* in the summer irradiation conditions and in conditions of prolonged good weather



## **ALL IN ONE 40 W**

LIGHTING		
Light output	6049 lm	
сст	6000 K	
Lifespan	100000 hours to LM80 specifications	
Number of LEDs	48 pcs	
Lightsource (type)	5050	



SOLAR PANEL		
Power	90 W	
Cells	16 monocrystalline cells	
Life span	80% power after 25 yers	

-			1387			-	
	-	-		-			35

STORAGE		
Battery capacity	550 Wh	
Working time	3-5 days	
Battery Service time	8 years at 70% DoD	



ENVIRONMENT		
Working temperature	-15°C to + 70°C	
Water resistance	IP65	

REMOTE CONTROL		
Wireless network	Zigbee Proprietary Wireless Network allows Remote Management and Control of Lights using Internet or GSM. One gateway (DTU) per 200 lights and all the gateways report to a central control room.	



MECHANICAL SPECIFICATIONS		
Reccommended top diameter of the pole	60-80 mm	
Reccommended pole height	6-10 m	
Net weight	25 Kg	
Package dimensions	1440 x 410 x 150 mm	
Bracket packing dimensions	380 x 260 x 200 mm	

